

# OXYDECOR<sup>®</sup> RUST

## Corten effect metal paint

### DESCRIPTION

Oxydecor<sup>®</sup> Rust Isoplam<sup>®</sup> is a particular decorative paint, which recreates the appearance of corten steel both as a visual aspect and to the touch.

It can be used both inside and outside.

Oxydecor<sup>®</sup> does not drip or stain.

It can be applied on concrete, drywall, wood, plastic, plaster, after the application of a coat of Deco Primer Finish Isoplam<sup>®</sup>.

On metal supports, it is recommended to degrease the surface and apply a coat of an anti-rust product (take into consideration the application of Isoplam<sup>®</sup> Plamfix79, an epoxy primer for difficult supports). If applied on very porous walls, it is recommended to apply a coat of Deco Primer Finish Isoplam<sup>®</sup>.

### APPLICATION

- Protect all the adjacent surfaces and objects that should not be treated with Oxyrust Isoplam<sup>®</sup>.
- Apply Deco Primer Finish Isoplam<sup>®</sup> with a long hair roller.
- After the complete drying, apply Oxyrust Primer with a long hair roller.
- Oxyrust Paint can be applied by brush or by spatula.
- Apply the first coat of Oxyrust Paint, let it dry and then apply the second coat.
- After the second coat, spray Oxyrust Oxidant in an irregular way.
- When Oxyrust Oxidant is dry or almost dry, spray Oxyrust Activator uniformly (it is recommended the use of protective gloves and goggles).
- You can increase the degree of oxidation by spraying several times on the support already treated.
- When the surface is completely dry, apply a coat of Oxyrust Protection, the final protection that stops the oxidation process and allows an easy cleaning. Alternatively, for greater protection even indoors, we recommend Plam Pol Water Mono opaque.
- Clean immediately all the equipment with water.
- Please note that spots, differences in tone and shadings are a natural characteristic of the realization.

Note: for outdoor applications, on surfaces exposed to humidity and to rain, it is recommended to protect with a cycle of one coat of Deco Epox W BI followed by two coats of Plam Pol Shower. It should be noted that the final protective products chosen will tone up the color making it slightly darker.

### TECHNICAL FEATURES

#### OXYRUST PAINT

PREPARATION

Ready to use, mix well before use.

APPLICATION:

By brush or spatula.

PACKAGING:

Supplied in packages of Lt 1, Lt 5, Lt 15

YIELD (on smooth surfaces):

With 1 Lt you can treat about 1,50-2,00 m<sup>2</sup> for 2 coats..

EXPIRY:

24 months in a cool and dry place in the unopened and sealed

**ISOPLAM S.R.L.**

Via E. Mattei, 4 – Z. I. Maser (TV) – Italia Tel. (+39) 0423 925023 www.isoplam.it

Certified company UNI EN ISO 9001:2015



package from the date on the package (the lot number indicates, in sequence, first 2 digits year/progressive number of the day/last 2 digits month).

CLEANING:  
APPLICATION TEMPERATURE:  
PROTECTION REQUIRED:  
CHARACTERISTICS:  
SECURITY:

Water.  
From +5°C to +35°C  
Masks, goggles and gloves.  
Avoid direct contact. Wash with soap and water.  
The product is not flammable.

### OXYRUST OXIDANT

PREPARATION:  
APPLICATION:  
PACKAGING  
YIELD:  
EXPIRY:

Ready to use.  
By spray.  
Available in packages of 1 Lt, 5 Lt, 25 Lt.  
With 1 Lt you can treat about 8-10 m<sup>2</sup>.  
12 months in a cool and dry place in the unopened and sealed package from the date shown on the package (the lot number indicates, in sequence, first 2 digits year/progressive number of the day/last 2 digits month).

APPLICATION TEMPERATURE:  
PROTECTION REQUIRED:  
CHARACTERISTICS:  
SECURITY:

From +5°C to +35°C.  
Masks, goggles and gloves.  
Slightly irritant and corrosive.  
The product is not flammable.

### OXYRUST ACTIVATOR

PREPARATION:  
APPLICATION:  
PACKAGING:  
YIELD:  
EXPIRY:

Ready to use.  
By spray.  
Available in packages of 1 Lt, 5 Lt, 25 Lt.  
With 1 Lt you can treat about 6-8 m<sup>2</sup>.  
24 months in a cool and dry place in the whole package and sealed by the date on the package (the lot number indicates, in sequence, first 2 digits year/progressive number of the day/last 2 digits month).

APPLICATION TEMPERATURE:  
PROTECTION REQUIRED:  
CHARACTERISTICS:  
SECURITY:

From +5°C to +35°C.  
Masks, goggles and gloves.  
Slightly irritant and corrosive.  
The product is not flammable.

### OXYRUST PROTECTION

PREPARATION:  
APPLICATION:  
PACKAGING:  
YIELD:  
EXPIRY:

Ready to use.  
By roller, brush or spray.  
Available in packages of 1 Lt, 5 Lt, 25 Lt.  
With 1 Lt you can treat about 5-7 m<sup>2</sup>.  
24 months in a cool and dry place in the unopened and sealed package, the lot number indicates the production date as follows, year/week/day.

APPLICATION TEMPERATURE:  
PROTECTION REQUIRED:  
CHARACTERISTICS:  
SECURITY:

From +5°C to +35°C  
Masks, goggles and gloves.  
Water-based product.  
The product is not flammable.

**IMPORTANT:**  
OXIDECOR® RUST ISOPLAM® products are formulated to be used as in the application above. All information contained in this sheet is based on the best practical and laboratory experiences. It is the customer's responsibility to verify that the product is suitable for the intended use. The manufacturer declines any responsibility for the results of incorrect applications.



It is advisable to always carry out tests on small surfaces before application. Data can be changed at any time. This sheet replaces and cancels previous ones. OXIDECOR® RUST ISOPLAM® products are intended for professional use. Isoplam Srl periodically organizes courses for its customers.

