

PLAM POLY WAX

Matt polyurethane wax for decorative surfaces

DESCRIPTION

Isoplam® Plam Poly Wax is a matt water-based protective for decorative surfaces. It is made of a polyurethane acrylic emulsion that makes a thin film that protects surfaces from wear and stains, keeping them perfect in time. Its water-based formulation makes it usable also in solvent free products cycles. Isoplam® Plam Poly Wax perfectly adheres on the surface on which it is applied, it does not peel, does not turn yellow and does not change the degree of surface slip.

USE OF FIELDS

Isoplam® Plam Poly Wax can be used for the protection of decorative surfaces, such as:

- Microverlay® ones;
- acidified and "nuvolato" ones;
- resin floorings;
- floorings treated with Plam Densifier, so that they mature correctly;
- resilient ones (rubber, pvc and linoleum);
- porous natural rock, cotto tiles, gres and clinker ones.

APPLICATION AND MANTEINANCE

Surfaces have to be accurately cleaned; there must not be oil or grease stains. Consult our technicians to find the proper solution for the preliminary cleaning of surfaces.

Apply with temperatures between +10°C and +35°. Shake well before use.

Isoplam® Plam Poly Wax has to be applied pure on a dry surface with an Isoplam® Wax Spreader in two thin and crossed coats (wait about an hour between one coat and the other).

Clean tools with water and soap.

It is possible to partially regenerate Plam Poly Wax film applying one coat in the portions that are particularly worn.

TECHNICAL FEATURES

ASPECT	milky liquid
SOLUBILITY	in water
SPECIFIC WEIGHT	1,02
DRY RESIDUE	18%
PH	9±0,5
ODOR	odorless

CONSUMATION

30-50 gr/m² per coat, depending on the porosity of the surface.

PACKAGES AND STORAGE

ISOPLAM® Plam Poly Wax is supplied in packages of 5Lt.
Store at temperatures between +10°C and +35°C. It fears the frost.
If properly stored, it keeps for 12 months in its original sealed packages.

SECURITY

Consult the security sheet before use. The product is intended for professional use only.

IMPORTANT:

The product PLAM POLY WAX is intended for the use as indicated above. Adding any other product will impair the final result. All information contained herein is based on the best practical experiences and laboratory research. It is the customer's responsibility to determine whether the product is suitable for the intended application. The manufacturer declines all responsibility on the results due to incorrect application of its products. The product shall always be tested on a small area before full scale application. This data sheet replaces all previous data sheets. ISOPLAM reserves the right to change the data on the data sheet at any time. PLAM POLY WAX is intended for professional use only. ISOPLAM provides frequent and on demand trainings for its customers. The use of ISOPLAM products without receiving the proper certification will be at the customer's own risk.

ISOPLAM S.R.L.

Via E. Mattei, 4 – Z. I. Maser (TV) – Italia
IDENTIFICAZIONE ISO 9001:2015

Tel. (+39) 0423 925023 Fax (+39) 0423 926119
Rev. 27/07/2016

www.isoplam.it