

# GROUT REMOVER

## Descaler gel for cementitious surfaces

### DESCRIPTION

Grout Remover Isoplam<sup>®</sup> is a concentrated descaler acid gel with an anti-limescale action that facilitates the removal of all types of limestone or cement deposits from various types of surfaces. Its particular gel formulation allows the product to stay longer on the surface to be treated and therefore increases its effectiveness on stains and encrustations. It is also used as a cleaning product (it also contains degreasing agents) and for the preparation of cement surfaces for subsequent treatments.

### FIELDS OF USE

Grout Remover Isoplam<sup>®</sup>:

- cleans and removes residues of cement grout from surfaces in granite, klinker, stone and all unpolished calcareous materials;
- helps to remove encrustations of various kinds from industrial cement floors;
- helps the removal of cement residues from Italian Terrazzo<sup>®</sup> flooring;
- opens the pores of the surfaces that will be treated with Plam Acid Isoplam<sup>®</sup>;
- opens the pores to allow the attachment of resinous coating treatments;
- can also be applied vertically, given its gelatinous consistency.

### APPLICATION

Grout Remover Isoplam<sup>®</sup> is ready to use. It is always recommended to carry out preliminary tests on a hidden part of the surface.

Apply with brush or Isoplam<sup>®</sup> squeegee taking care to leave a layer of about 1 mm and leave to act for 20-30 minutes (an effervescent effect could be created). Then rinse thoroughly with water.

If the result is not satisfactory, it is possible to reapply Grout Remover again. Grout Remover is not applied: on metal parts, on slate surfaces, on shiny surfaces.

It is recommended not to let the product dry or remain on the surface for more than 30 minutes: in this case the surface will take on a yellowish color. If this happens, the halos can be removed with the Sbiancante per Acido Isoplam<sup>®</sup>.

### CONSUMPTIONS

Consumption is about 0,2 Lt/m<sup>2</sup> (yield about 5 m<sup>2</sup>/Lt). The same can vary considerably depending on the thickness of the applied product layer.

### PACKAGING, STORAGE AND SAFETY

Grout Remover Isoplam is supplied in 5 Lt packs.

The product must be stored in a cool and dry place, with temperatures between +5°C and +30°C.

If properly stored, it is guaranteed for 12 months from the date shown on the package (the lot number indicates, in sequence, year/week/day). The product cannot stand frost.



## **SAFETY**

The product is intended for professional use only.  
Consult the safety data sheet before use.

### **IMPORTANT**

GROUT REMOVER product is formulated to be used as in the application indicated above. The addition of any other product compromises the final result of the surface and the safety of the operator.

All the information contained in this sheet is based on the best practical and laboratory experiences. It is the customer's responsibility to verify that the product is suitable for the intended use.

The manufacturer declines all responsibility for the results of incorrect applications. It is always recommended to carry out tests on small surfaces before application. The data can be changed at any time. This sheet replaces and cancels the previous ones.

The GROUT REMOVER product is intended for professional use.

Isoplam Srl periodically organizes courses for its customers who request them. Anyone who uses these products without being enabled does so at their own risk.